



**MEMOLUB® HPS 25 bar**

- Single or multi-point
- 25 bar pressure
- Remotely installed up to 8 meters
- Can be used with 1 or up to 8 outlets

With a 25 bar expulsion pressure, this model is the most versatile unit in its range.

Frequency is set once and then it is regulated by the MEMO. Maintenance staff do not need to worry about set up of the unit when lubricant refills are completed.

Ideal for all types of industry applications: bearings, open gears, chains, rollers, etc.

Most economical device in the market. The HPS is easily refilled by simply replacing the grease cartridge and battery pack. The HPS has a limited impact on the environment.

The unit is supplied with a check valve, timing rings, stroke limiting washers and an UV extra protection cover to suit.



Technical Specifications	
Cartridge Capacity	120cc, 240cc or 480cc
Maximum stroke pressure	25 bar / 250 psi
Batteries	4.5V Alkaline Battery
Remote Installation	Up to 8 meters (single point) – Ø 8mm tubing
Lubricants	Oil and grease (up to NLGI 2 with an oil base between 100 and 460cSt)
Operating Temperature	-15°C to 50°C
Connections	¼ BSP
Distribution	Progressive distribution block up to 8 points*

\*See distributor blocks for more information

MEMO Adjustments	○○○	○○	○○	○	○○	○	○
Operations/day	24	12	4	2	1.5	1	0.5
Daily Output	14.4 cc	7.2 cc	2.4 cc	1.2 cc	0.9 cc	0.6 cc	0.3 cc

Product Ordering	
Product	Part Code
Memolub HPS 120cc	HPS-S
Memolub HPS 240cc	HPS-M
Memolub HPS 480cc	HPS-G